

## IBM Deskstar™ 120GXP hard disk drives



---

### Highlights

---

- **Provides industry-leading performance at 7,200rpm, 592Mbits/sec internal transfer rate, and 8.5ms average seek time. These combine to enable leading sustained data rate of up to 48MB/sec.**
- **Increases in disk capacity by 100 percent over previous generation**
- **Capacities range from up to 40GB to 120GB**
- **Designed to protect user data with ramp load/unload of the heads**
- **Thermal monitor helps provide accurate data writes and reads over the full system temperature range**

### ■ **Meets PC Design Checklist for Windows® XP**

### ■ **Industry-leading low power**

The Deskstar 120GXP incorporates both new and proven technologies to boost system performance. This drive provides the capacity and performance to handle a wide range of advanced desktop and audio/video applications. Additionally, features such as low acoustics, low power, and Tagged Command Queuing make this drive ideal for non-PC, high performance, special applications.

### Technology for capacity and performance

- *Antiferromagnetically coupled (AFC) media enables higher capacities per square inch of data surface.*
- *Glass disks provide smoother media for the ever-shrinking bit size.*
- *Three-disk design provides leading 120GB capacity at 7,200rpm.*
- *IBM-designed onboard processor provides faster speeds than the previous generation.*
- *Advanced buffer management bursts data to the system at up to 100MB/sec.*
- *Enhanced servo system provides reliable head positioning.*

AFC and glass disk technologies enable increased areal density. Thus, the Deskstar provides the necessary capacities using fewer heads and disks, which means fewer components and better reliability. The superior areal density combines with the faster processor and streamlined cache buffer to enable award-winning performance for both the Deskstar and your system. Enhancements to the servo system and thermal monitor help to enable accurate data storage and retrieval.

Deskstar 120GXP matches the drive capacity and performance guidelines for Microsoft® Windows XP—40GB minimum and 7,200rpm.

### Technology for reliability

- *Load/unload head ramps*
- *Glass media*
- *Ceramic spindle motor bearings*
- *Differential read channel*
- *Internal thermal monitor*
- *Drive Fitness Test (DFT)*
- *S.M.A.R.T Self Test*

These combined technologies enable popular capacity points and are also designed to increase reliability. Deskstar drives continue to utilize proven IBM technology such as TrueTrack servo and No-ID sector formatting.

## IBM Deskstar 120GXP at a glance

### Product name **Deskstar 120GXP**

Model names	IC35L120AVVA07-0 IC35L080AVVA07-0 IC35L040AVVA07-0
-------------	--

### Configuration

Interface	ATA-100 compatible
Capacity (GB)	120/80/40
Sector size (bytes)	512
Recording zones	31
Data heads (physical)	6/4/2
Data disks	3/2/1
Max. areal density (Gbits/sq. inch)	29.7
Max. recording density (BPI)	524,000
Track density (TPI)	56,700

### Performance

Data buffer	2MB
Rotational speed (rpm)	7,200
Latency average (ms)	4.17
Media transfer rate (max. Mbits/sec)	592
Interface transfer rate (max. MB/sec)	100
Sustained data rate (MB/sec)	48 to 23 (Zones 0-30)

### Seek time (read, typical)

Average (ms)	8.5
Track-to-track (ms)	1.2
Full-track (ms)	15.0

### Reliability

Error rate (non-recoverable)	1 in 10 <sup>13</sup>
Start/stops (at 40° C)	40K
Recommended power-on hours (monthly)	333

### Acoustic

Idle (Bels)	3.0 (1 disk) 3.0 (2 disks) 3.1 (3 disks)
-------------	--

### Power

Requirement	+5 VDC (+/- 5%), +12 VDC (+10%/-8%)
-------------	-------------------------------------

### Dissipation

Startup current (max. A)	2.0 (+12V) & 0.74 (+5V)
Idle (W)	6.7 (3 disks)

### Physical size

Height (mm)	25.4
Width (mm)	101.6
Depth (mm)	146
Weight (max. g)	560 (1 disk) 575 (2 disks) 590 (3 disks)

### Environmental characteristics

Operating	
Ambient temperature	5° to 55° C
Relative humidity (non-condensing)	8% to 90%
Max. wet bulb (non-condensing)	29.4° C
Shock (half sine wave, 2ms)	55G
Vibration (random (RMS))	0.67G for horizontal 0.56G for vertical

### Non-operating

Ambient temperature	-40° to 65° C
Relative humidity (non-condensing)	5% to 95%
Max. wet bulb (non-condensing)	35° C
Shock (half sine wave, 2ms)	400G (1 or 2 disks); 350 (3 disks)
Vibration (random (RMS))	1.04G rms (XYZ)

<sup>1</sup> This product data does not constitute a warranty. Questions regarding IBM warranty terms or the methodology used to derive this data should be referred to an IBM representative.

<sup>2</sup> GB equals one billion bytes when referring to hard drive capacity; accessible capacity may be less.

## For more information

Internet and e-mail:


- [ibm.com/harddrive](http://ibm.com/harddrive)
- [drive@us.ibm.com](mailto:drive@us.ibm.com)

IBM TECH FAX document server:

- 408-256-5418 (requires touch-tone phone)
- International callers must call from a fax machine

IBM hard drive product information:

- 1-888-IBM-5214
- 507-253-4110



© International Business Machines Corporation 2001

IBM Storage Technology Division  
5600 Cottle Road  
San Jose, CA 95193

Produced in the United States  
11/01  
All rights reserved

IBM is a registered trademark and Deskstar is a trademark of International Business Machines Corporation.

Microsoft Windows NT, and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other names are trademarks or registered trademarks of their respective owners.

Product description data represents design objectives and is provided for comparative purposes; actual results may vary depending on a variety of factors. Product claims are true as of the date of first printing. Data is subject to change without notice. IBM development plans are subject to change at any time without prior notice. Reference in this publication to IBM products, programs, or services do not imply that IBM intends to make them available in all countries in which IBM operates.

TECHFAX# 7020