



Adobe Binary Screen Font Files Specification

Adobe Developer Support

Version 2.0

31 March 1992

Adobe Systems Incorporated

Corporate Headquarters
1585 Charleston Road PO Box 7900
Mountain View, CA 94039-7900
(415) 961-4400 Main Number
(415) 961-4111 Developer Support
Fax: (415) 961-3769

Adobe Systems Europe B.V.
Europlaza
Hoogoorddreef 54a
1101 BE Amsterdam Z-O, Netherlands
+31-20-6511 200
Fax: +31-20-6511 300

Adobe Systems Eastern Region
24 New England
Executive Park
Burlington, MA 01803
(617) 273-2120
Fax: (617) 273-2336

Adobe Systems Japan
Swiss Bank House 7F
4-1-8 Toranomon, Minato-ku
Tokyo 105, Japan
81-3-3437-8950
Fax: 81-3-3437-8968

Copyright ©1987-1989, 1992 by Adobe Systems Incorporated. All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of the publisher. Any software referred to herein is furnished under license and may only be used or copied in accordance with the terms of such license.

The PostScript logo, Adobe, and the Adobe logo are trademarks of Adobe Systems Incorporated which may be registered in certain jurisdictions. IBM PC is a registered trademark of International Business Machines Corporation. Other brand or product names are the trademarks or registered trademarks of their respective holders.

This publication and the information herein is furnished AS IS, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies, makes no warranty of any kind (express, implied or statutory) with respect to this publication, and expressly disclaims any and all warranties of merchantability, fitness for particular purposes and noninfringement of third party rights.



Contents

Adobe Binary Screen Font Files Specification 1

1 Introduction 1

2 File Format 1

Appendix: Changes Since Earlier Versions 5

Index 7

Adobe Binary Screen Font Files Specification

1 Introduction

This document describes Adobe Systems' binary screen font format, also called the ABF format. The format is a binary encoding of Adobe Systems' character bitmap distribution format, an ASCII-encoded, human-readable file format. You should refer to the document *Character Bitmap Distribution Format* (Adobe part number LPS5005) for more details.

2 File Format

Each file is a sequence of 8-bit bytes. File names, by convention, end with the extension *.abf*. The first byte of the file indicates the byte ordering of the information in the file.

- A value of 1 indicates low-byte-first (for example, IBM PC[®]) byte order.
- A value of 2 indicates high-byte first byte order. The second byte of the file indicates the “form factor” of the character bitmap.
- A value of 1 indicates that the bitmap should be accessed as an array of 8-bit words to correctly address the bits of the character.
- A value of 2 indicates that the bitmap should be accessed as an array of 16-bit words.
- A value of 4 indicates the bitmap should be accessed as an array of 32-bit words.

In all three form factors, the most significant bits of the word represent the left-most bits of the character.

The remainder of the file consists of four sections. The first section describes the font as a whole and corresponds to the entries in the character bitmap distribution format up to and including the CHARS entry. The second section

is an array of records, one record per character described in the file. Each record corresponds roughly to the information between a STARTCHAR - ENDCHAR entry in the distribution format.

There are three minor deviations from an exact correspondence.

- The SWIDTH entry, which contains printer width information, is not encoded in the binary format.
- The bitmap for the character is not contained within the record itself. Rather, the record contains a reference to the character contained in the third section of the file.
- The name of the glyph is not contained in the record. As with the bitmap, a reference within the record points to the string containing the glyph name.

The bitmaps for the characters are stored in what is commonly referred to as a “strike” format. A strike is a rectangular pixel array whose height is the height of the tallest character in the font and whose width is the sum of the widths of all the characters. Individual characters are located within the strike by a bit-offset from the beginning of the bitmap array to the beginning of the character. The width of each character in the Adobe™ strike is the width of the bounding box of the character.

Table 1 lists all of the fields in the file, the size of the field, and the corresponding keyword in the character distribution file format. In the **Size** column, **B** indicates an 8-bit byte. **W** indicates a 16-bit word, and **L** indicates a 32-bit long word. If the size code (**B**, **W**, or **L**) is followed by a number *i* enclosed in brackets, then the field is composed of an array of *i* items. The file *makefont.h* contains C-language declarations for the important data structures.

Table 1 *Binary screen font files*

<i>Field</i>	<i>Size</i>	<i>Keyword</i>	<i>Comments</i>
Order	B	N.A.	Byte order of info in file
Bitmap-Type	B	N.A.	Is the bitmap an array of bytes, words, or long words?
Version	W	STARTFONT	Version number. The notation STARTFONT V.R maps to Version = 256 * V + R
Copyright	B[60]	COMMENT	Copyright string.
Name	B[60]	FONT	Font name string.
Point-Size	W	SIZE	
XResolution	W	SIZE	
YResolution	W	SIZE	
BBox	W[4]	FONTBOUNDINGBOX	
NumberOfChars	W	CHARS	Number of entries in the second section of the file containing character descriptions.
RowBytes	W	N.A.	Number of bytes in each row of the strike bitmap.
SizeOfNames	W	N.A.	Number of bytes in the fourth section of glyph names.
OffsetToChars	L	N.A.	Offset from beginning of file to the fourth section of glyph names.
OffsetToStrike	L	N.A.	Offset from beginning of file to third section of file (strike).
CharDescriptions	W[8 * NumberOfChars]		Array with 8 words per entry. Subfields are:
Width	W	DWIDTH	
CharCode	W	ENCODING	
BBox	W[4]	BBX	
OffsetToName	W	STARTCHAR	Offset from beginning of names section to beginning of zero-terminated string name.
BitOffset	W	BITMAP	Bit offset from beginning of second section to beginning of character bitmap.
CharBitmaps	B[RowBytes * BBox.Height]		The actual bits
NamesArray	B[SizeOfNames]		Character names represented as zero-terminated strings.

Figure 1 *Adobe binary screen font file format*

Offset	
0:	Order (B) BitmapType (B)
2:	Version
4:	Copyright
64:	Name
124:	PointSize
126:	XResolution
128:	YResolution
130:	BBox Width Height LeftOrigin BottomOrigin
138:	NumberOfChars
140:	RowBytes
142:	SizeOfNames
144:	OffsetToChars (L)
148:	OffsetToNames (L)
152:	OffsetToStrike (L)
	CharDescriptions
	CharBitmaps
	NamesArray



Appendix: Changes Since Earlier Versions

Changes since the January 16, 1989 version

- Document was reformatted in the new document layout and minor editorial changes were made.



Index

A

.abf 1

ABF format 1–3

Adobe binary screen font format. *See*
ABF format

B

binary screen font files 3

S

strike format 2